

ROLLSROLLER® ENTRY

ENTRY RANGE	ROLLSROLLER ENTRY 280	ROLLSROLLER ENTRY 340	
	280/145E	340/145E	340/170E
Bed length (mm)	2800	3400	3400
Bed width (mm)	1450	1450	1700
Length of working area (mm)	2500	3100	3100
Width of working area/roller width (mm)	1400	1400	1630
Overall width incl. Glide beam (mm)	1685	1685	1985
Overall height incl. Glide beam (mm)	1340	1340	1340
Max. thickness of sign substrate (mm)	60	60	60
ExtRoller adjustment*	X	X	X
Work height table bed	875	875	875
Work height adjustment, 750-1100mm	X	X	X
Power Supply Height Adjustment	X	X	X
Bed surface	Aluminium & Cutting mat	Aluminium & Cutting mat	Aluminium & Cutting mat
Removable AL Flatbed top + Cutting mat	X	X	X
LED Light Table	X	X	X
Illumination light tubes	X	X	X
Power Supply (if illuminated)	X	X	X
Roll holder for Glide Beam	✓	✓	✓
Roll holder for bed end	✓	✓	✓
Side trays	X	X	X
Side tray roll holder	-	-	-
Storage trays	X	X	X
Wheels	4	4	4
Machine feet	✓	✓	✓
Required air pressure	6-8bar / 87-116psi	6-8bar / 87-116psi	6-8bar / 87-116psi
Silent compressor 45db	✓	✓	✓
Weight (kg)	250	270	305
Stop static kit cord and magnet	✓	✓	✓
Warranty	Up to 2 years	Up to 2 years	Up to 2 years



ROLLSROLLER®
FLATBED APPLICATOR

✓ Yes ✓ Optional X No / Not applicable * to enable substrates up 100mm



the sign company's company

materials supply | signs & display | hardware

www.williamsmith.co.uk



@William_Smiths

01833 690305

www.vehiclewrapfilms.co.uk



/WilliamSmith1832

info@williamsmith.co.uk



William Smith
established 1832